

---

<b>Company name</b>	Lindab Steel AB	<b>E-mail</b>	steel@lindab.se
<b>Address</b>	Stålhögavägen 117 269 82 Båstad	<b>Registration No</b>	556237-8660
<b>Telephone No</b>	+46 (0)431-850 00	<b>Contact</b>	Sales department
<b>Fax No</b>	+46 (0)431-853 51	<b>Internet</b>	www.lindab.se
<b>Environmental work</b>	Certified management systems in accordance with ISO 9001:2008 and ISO 14001:2004.		

---

## Copper

### Declaration of contents

Copper plate in conformity with SS-EN 1172.

#### Dimensions

Thickness: 0,50-1,00 mm.

#### Raw material origin

The purchase is mainly made from mills within the EU.

### Production

#### Energy consumption and emission

Electricity is used for operating the production machinery and internal transports. Natural gas is heating the production premises. The total electricity consumption is 9,95 kWh per produced ton.

No emission to water or air.

### Distribution of finished product

#### Production locality

Grevie, Sweden

#### Distribution

The product is mainly carried by long distance truck.

#### Packaging

The product is normally packaged with combinations of polyethylene film, paper, board, steel sheet/ring, steel/plastic straps and pallet depending on the destination and the customer's requirements. Some of the packaging can be reused, while the remainder is sorted at source and is returned for recycling.

### The Construction phase

No environmental influence

#### Maintenance

Maintenance as cleaning and washing may be necessary to preserve the surface and appearance of the corrosion resistant properties.

The plate surface can be influenced by the surrounding environment. Copper may interact with other metals at the contact surfaces.

#### Material recovery

Copper plate can be 100 % recycled. Utilized waste from building, maintenance and demolition work and workshops should be separated and returned to the steel industry through the scrap trade.

### Working Environment

With conventional use the copper plate don't involve any health risks. Respiratory protection should be used when grinding and welding.